

AEROGREEN 4130 CLEANER AND DEGREASER



PRODUCT DESCRIPTION:

AEROGREEN 4130 CLEANER AND DEGREASER is a high - pressure cleaner & degreaser is formulated for pressure washing applications in industrial, commercial, and for both interior and exterior environments. Quickly and easily removes built-up dirt, oils, greases, fuel residue, mold, mildew, fungus, algae along with other contaminates from the surface. The use of the cleaner will prevent the return of mold and mildew. Using Aerogreen 4130 will significantly reduce surface contamination and increase efficiency over just plain water washing.

FEATURES:

- Compatible with all types of pressure washers
- Heavy-duty cleaning power
- No VOC's
- Removes mold, mildew, and algae
- Foam cannon compatible

BENEFITS:

- Versatile application options
- Suitable for cleaning wide range of surfaces
- Applicable for exterior & interior applications
- Will not harm landscaping and gardens
- Biodegradable, non-toxic, and free of Bleach
- Safe for use on equipment & vehicles

WHAT IS IT:

AEROGREEN 4130 CLEANER AND DEGREASER is formulated with ingredients that have strong cleaning properties and can penetrate and lift away stubborn residues, leaving surfaces clean and free from grease and grime. It is formulated to clean surfaces prior to painting without leaving a soapy residue behind that interferes with coating adhesion developed to clean surfaces prior to painting and will not leave a soapy residue behind that interferes with coating adhesion.

WHAT IS IT USED FOR:

It is formulated for pressure washing applications in industrial, commercial, and for both interior and exterior environments. Aerogreen 4130 is essential for maintaining cleanliness and removing stains from surfaces. It can be used as a cleaner prior to inspection and repairs for equipment by removing the oils, dirt, grease, waxes, polishing compounds, salts, soluble oils, drilling, and cutting compounds from the surface. Aerogreen 4130 can be safely used in between primer and topcoat and as a final cleaning shipping.

HOW IT WORKS:

It reduces surface tension, dissolves or breaks down substances, suspends oily residues, and lifts and loosens dirt. Aerogreen 4130 utilizes a combination of chemical properties and mechanisms to achieve thorough and efficient cleaning results.





APPLICATION GUIDELINES:

Ambient temperature: Apply between 40-90 degrees °F

Use as pre-soak: Dilute Aerogreen 4130 3:1 with water. Spray, using a pump sprayer the area to be cleaned. Let soak for 10-15mins. Rinse using a pressure washer (1000-3000psi). Dry with an air-hose or clean cloth prior to painting.

Use with a pressure washing system: Wet the surface to be cleaned with water. Set dilution jets between 5-20%, depending upon the level of contaminants to be removed. Drop the feeder hose into Aerogreen 4130 solution to draw into the pressure washer. Clean the area and then dry it with air or use a clean cloth.

Adjust the pressure: To wash dirt, grime and soils keep the pressure level between 1500psi and 1800psi.

Choosing the correct nozzle: Wide-Fan nozzles are often preferred when pressure washing exterior painted surfaces. Available in yellow (15°), green (25°), white (40°), or black (65°) fan tips. Red (0°) is not recommended for washing.

Divide large areas: Break large areas into sections and wash from the top down, using long strokes. To avoid damaging walls, keep the nozzle at a 45° angle and spray from a minimum distance of 12 inches. If pressure is increased, move the nozzle further away from the surface. Scrub heavy soiled areas: Use a rotating scrub brush, power broom, or a sponge in conjunction with Aerogreen concentrate, to remove stains or pre-treat areas before final power washing.

COVERAGE

Over 800 SQFT when mixed 3:1. (3 gallons water & 1 gallon Aerogreen 4130) with use of pump sprayer

USE IT ON THE FOLLOWING SURFACES:

















Stucco

Steel

Porcelain

Stone

Brick

Vinyl

Aluminum

Wood

SPECIFICATIONS:

•	Flammable/Combustible	No
•	Water Solubility	100%
•	Contains Terpenes	No
•	SCAQMD Certified	Yes
•	lbs/glpH @ Concentrate	12.0-12.3
•	pH @ 3:1 Dilution	10.0-11.0
•	Density lbs. /per gal	8.9 lbs/gl

ORDERING INFORMATION

Aerogreen Product Number		
4130P	5 Gallon Pail	
4130D	55 Gallon Drum	
4130T275	275 Gallon Tote	
4130T330	330 Gallon Tote	

SAFETY/CAUTION:

Rubber gloves are recommended to prevent drying of the skin. Goggles are recommended to protect eyes if splashing is expected. When heated above 125 F, mechanical or local ventilation is required. When using product in steam cleaning and/or pressure washing application wear a rain suit and boots to keep clothes dry. Harmful if swallowed. Avoid getting into eyes. If contact occurs, flush with running water. If irritation persists, get medical attention. May cause dryness of skin with prolonged use, wash hands with cold water and apply hand lotion.

